

# BIG BIKE PARTS® INSTALLATION INSTRUCTIONS

Copyright© 2001 by Big Bike Parts, Inc.  
No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.©

PART NO. 52-610, 52-687 & 52-703 TOUR LUGGAGE RACK  
HONDA GL1800 GOLD WING

Revised 01/11/07

ITEMS REQUIRED 4MM ALLEN WRENCH SMALL POINT MARKING PEN  
3/4" MASKING TAPE CENTER PUNCH & HAMMER  
1/4" DRILL BIT & ELECTRIC DRILL

## INSTALLATION:

1. POSITION RACK SQUARELY ON TRUNK LID AS FAR FORWARD AS POSSIBLE WITHOUT ALLOWING ENDS TO RUB ON PASSENGER BACKREST SECTION.
2. LIFT RACK SLIGHTLY AND PLACE THREE 3" - 4" PIECES OF MASKING TAPE UNDER EACH OF THE REAR LEGS. (FIG B).
3. USE A MARKING PEN TO OUTLINE EACH OF THE FOUR MOUNTING LEGS ONTO THE TAPE STRIPS.
4. REPOSITION THE RACK OVER THE MARKED CIRCLES TO MAKE CERTAIN THE RACK IS IN THE EXACT LOCATION YOU DESIRE. (IF NECESSARY, REMARK ANY INCORRECT CIRCLE MARKINGS.)
5. SET THE RACK ASIDE. USING THE CENTER PUNCH, MARK THE HOLE CENTERS IN THE FOUR MOUNTING LOCATIONS. DRILL 1/4" HOLES THROUGH THE LID.
6. CAREFULLY REMOVE ALL MASKING TAPE FROM LID AND LEGS. REMOVE THE FOUR RUBBER BOOTS AND ATTACH RACK ACCORDING TO FIGURE A.

### **IMPORTANT:**

1. DO NOT OVER TIGHTEN THE (4) MOUNTING SCREWS –THERE IS A SPACE BETWEEN THE INNER & OUTER TRUNK LID. OVER TIGHTENING MAY CAUSE DAMAGE TO THE OUTER LID.
2. THIS RACK WAS DESIGNED TO SAFELY CARRY A WEIGHT LOAD OF TEN POUNDS OVERLOADING THE RACK MAY CAUSE DAMAGE TO THE TRUNK LID.

